



**AiP74LVC273**  
**Octal D-type flip-flop with reset;**  
**positive-edge trigger**

**Product Specification**

**Specification Revision History:**

<b>Version</b>	<b>Date</b>	<b>Description</b>
2023-07-A0	2023-07	New
2023-11-A1	2023-11	Parameter modification



# Contents

<b>1、 General Description.....</b>	<b>1</b>
<b>2、 Block Diagram And Pin Description .....</b>	<b>3</b>
2.1、 Block Diagram.....	3
2.2、 Pin Configurations .....	4
2.3、 Pin Description .....	4
2.4、 Function Table.....	5
<b>3、 Electrical Parameter .....</b>	<b>5</b>
3.1、 Absolute Maximum Ratings .....	5
3.2、 Recommended Operating Conditions .....	5
3.3、 Electrical Characteristics .....	5
3.3.1、 DC Characteristics 1 .....	5
3.3.2、 DC Characteristics 2.....	6
3.3.3、 AC Characteristics 1 .....	7
3.3.4、 AC Characteristics 2.....	8
<b>4、 Testing Circuit .....</b>	<b>9</b>
4.1、 AC Testing Circuit.....	9
4.2、 Test Data.....	9
4.3、 AC Testing Waveforms .....	10
4.4、 Measurement Points.....	11
<b>5、 Package Information .....</b>	<b>12</b>
5.1、 SOP20.....	12
5.2、 TSSOP20 .....	13
5.3、 DHVQFN20.....	14
<b>6、 Statements And Notes .....</b>	<b>15</b>
6.1、 The name and content of Hazardous substances or Elements in the product .....	15
6.2、 Notes.....	15



## 1、 General Description

The AiP74LVC273 consists of eight edge-triggered, D-type flip-flops with individual Dn inputs and Qn outputs.

The input can be driven from either 3.3V or 5V devices. This feature allows the use of this device in a mixed 3.3V and 5V environment.

### Features:

- Supply voltage range:1.2V to 3.6V
- Inputs accept voltages up to 5.5V
- $\pm 24\text{mA}$  output drive at 3.0V
- High-impedance when  $V_{CC}=0\text{V}$
- Temperature range:-40°C to +125°C
- Packaging information: SOP20/TSSOP20/DHVQFN20

**Ordering Information:****Tube packing specifications:**

Part number	Packaging form	Marking code	Tube quantity	Boxed tube quantity	Boxed quantity	Notes
AiP74LVC273SA20.TB	SOP20	74LVC273	35 PCS/tube	80 tube/box	2800 PCS/box	Dimensions of plastic enclosure: 12.8mm×7.5mm Pin spacing: 1.27mm
AiP74LVC273TA20.TB	TSSOP20	74LVC273	70 PCS/tube	200 tube/box	14000 PCS/box	Dimensions of plastic enclosure: 6.5mm×4.4mm Pin spacing: 0.65mm

**Reel packing specifications:**

Part number	Packaging form	Marking code	Reel quantity	Boxed reel quantity	Notes
AiP74LVC273SA20.TR	SOP20	74LVC273	2000 PCS/reel	2000 PCS/box	Dimensions of plastic enclosure: 12.8mm×7.5mm Pin spacing:1.27mm
AiP74LVC273TA20.TR	TSSOP20	74LVC273	4000 PCS/reel	8000 PCS/box	Dimensions of plastic enclosure: 6.5mm×4.4mm Pin spacing:0.65mm
AiP74LVC273QE20.TR	DHVQFN20	74LVC273	3000 PCS/reel	3000 PCS/box	Dimensions of plastic enclosure: 4.5mm×2.5mm Pin spacing:0.5mm

Note: If the physical information is inconsistent with the ordering information, please refer to the actual product.



## 2、Block Diagram And Pin Description

### 2.1、Block Diagram




Figure 1. Functional diagram





Figure 2. Logic diagram



## 2.2、Pin Configurations



Note: (1) This is not a supply pin. The substrate is attached to this pad using conductive die attach material. There is no electrical or mechanical requirement to solder this pad. However, if it is soldered, the solder land should remain floating or be connected to GND.

## 2.3、Pin Description

Pin No.	Pin Name	Description
1	MR	Master reset input (active LOW)
2	Q0	data output
3	D0	data input
4	D1	data input
5	Q1	data output
6	Q2	data output
7	D2	data input
8	D3	data input
9	Q3	data output
10	GND	ground (0V)
11	CP	clock input ( LOW-to-HIGH; edge-triggered)
12	Q4	data output
13	D4	data input
14	D5	data input
15	Q5	data output
16	Q6	data output
17	D6	data input
18	D7	data input
19	Q7	data output
20	V <sub>CC</sub>	supply voltage



## 2.4、Function Table

Operating modes	Input			Output
	MR	CP	Dn	Qn
Reset (clear)	L	X	X	L
Load '1'	H	↑	h	H
Load '0'	H	↑	l	L

Note:

H = HIGH voltage level;

h = HIGH voltage level one set-up time prior to the HIGH-to-LOW LE transition

L = LOW voltage level;

l = LOW voltage level one set-up time prior to the HIGH-to-LOW LE transition

↑ = LOW-to-HIGH clock transition

## 3、Electrical Parameter

### 3.1、Absolute Maximum Ratings

(T<sub>amb</sub>=25°C, All voltage referenced to V<sub>SS</sub>, unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Max.	Unit
supply voltage	V <sub>CC</sub>	-	-0.5	+6.5	V
input voltage	V <sub>I</sub>	-	-0.5	+6.5	V
output voltage	V <sub>O</sub>	Active mode	-0.5	V <sub>CC</sub> +0.5	V
		Power-down mode; V <sub>CC</sub> =0V	-0.5	+6.5	V
supply current	I <sub>CC</sub>	-	-	100	mA
ground current	I <sub>GND</sub>	-	-100	-	mA
input clamping current	I <sub>IK</sub>	V <sub>I</sub> < 0V	-50	-	mA
output current	I <sub>O</sub>	V <sub>O</sub> =0V to V <sub>CC</sub>	-	±50	mA
output clamping current	I <sub>OK</sub>	V <sub>O</sub> > V <sub>CC</sub> or V <sub>O</sub> < 0V	-	±50	mA
storage temperature	T <sub>stg</sub>	-	-65	+150	°C
Soldering temperature	T <sub>L</sub>	10s	260		°C

### 3.2、Recommended Operating Conditions

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
supply voltage	V <sub>CC</sub>	-	1.2	-	3.6	V
input voltage	V <sub>I</sub>	-	0	-	5.5	V
output voltage	V <sub>O</sub>	Active mode	0	-	V <sub>CC</sub>	V
		Power-down mode; V <sub>CC</sub> =0V	0	-	5.5	V
ambient temperature	T <sub>amb</sub>	-	-40	-	+125	°C

### 3.3、Electrical Characteristics

#### 3.3.1、DC Characteristics 1

(T<sub>amb</sub>=-40°C to +85°C, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	V <sub>CC</sub>	Conditions	Min.	Typ.	Max.	Unit
HIGH-level	V <sub>IH</sub>	1.2V	-	1.08	-	-	V



input voltage		1.65V to 1.95V	-	$0.65 \times V_{CC}$	-	-	V
		2.3V to 2.7V	-	1.7	-	-	V
		2.7V to 3.6V	-	2.0	-	-	V
LOW-level input voltage	$V_{IL}$	1.2V	-	-	-	0.12	V
		1.65V to 1.95V	-	-	-	$0.35 \times$	V
		2.3V to 2.7V	-	-	-	0.7	V
		2.7V to 3.6V	-	-	-	0.8	V
HIGH-level output voltage	$V_{OH}$	1.65V to 3.6V	$I_O = -100\mu A$	$V_{CC} - 0.2$	-	-	V
		1.65V	$I_O = -4mA$	1.2	-	-	V
		2.3V	$I_O = -8mA$	1.8	-	-	V
		2.7V	$I_O = -12mA$	2.2	-	-	V
		3.0V	$I_O = -18mA$	2.4	-	-	V
		3.0V	$I_O = -24mA$	2.2	-	-	V
LOW-level output voltage	$V_{OL}$	1.65V to 3.6V	$I_O = 100\mu A$	-	-	0.2	V
		1.65V	$I_O = 4mA$	-	-	0.45	V
		2.3V	$I_O = 8mA$	-	-	0.6	V
		2.7V	$I_O = 12mA$	-	-	0.4	V
		3.0V	$I_O = 24mA$	-	-	0.55	V
input leakage	$I_I$	3.6V	$V_I = 5.5V$ or GND	-	-	$\pm 5$	$\mu A$
supply current	$I_{CC}$	3.6V	$V_I = V_{CC}$ or GND; $I_O = 0A$	-	-	10	$\mu A$
additional supply current	$\Delta I_{CC}$	2.7V to 3.6V	per input pin; $V_I = V_{CC} - 0.6V$ ; $I_O = 0A$	-	-	500	$\mu A$

### 3.3.2、DC Characteristics 2

( $T_{amb} = -40^\circ C$  to  $+125^\circ C$ , voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	$V_{CC}$	Conditions	Min.	Typ.	Max.	Unit
HIGH-level input voltage	$V_{IH}$	1.2V	-	1.08	-	-	V
		1.65V to 1.95V	-	$0.65 \times V_{CC}$	-	-	V
		2.3V to 2.7V	-	1.7	-	-	V
		2.7V to 3.6V	-	2.0	-	-	V
LOW-level input voltage	$V_{IL}$	1.2V	-	-	-	0.12	V
		1.65V to 1.95V	-	-	-	$0.35 \times$	V
		2.3V to 2.7V	-	-	-	0.7	V
		2.7V to 3.6V	-	-	-	0.8	V
HIGH-level output voltage	$V_{OH}$	1.65V to 3.6V	$I_O = -100\mu A$	$V_{CC} - 0.3$	-	-	V
		1.65V	$I_O = -4mA$	1.05	-	-	V
		2.3V	$I_O = -8mA$	1.65	-	-	V
		2.7V	$I_O = -12mA$	2.05	-	-	V
		3.0V	$I_O = -18mA$	2.25	-	-	V
		3.0V	$I_O = -24mA$	2.0	-	-	V
LOW-level	$V_{OL}$	1.65V to 3.6V	$I_O = 100\mu A$	-	-	0.3	V



output voltage		1.65V	$I_O = 4\text{mA}$	-	-	0.65	V
		2.3V	$I_O = 8\text{mA}$	-	-	0.8	V
		2.7V	$I_O = 12\text{mA}$	-	-	0.6	V
		3.0V	$I_O = 24\text{mA}$	-	-	0.8	V
input leakage	$I_I$	3.6V	$V_I = 5.5\text{V}$ or GND	-	-	$\pm 20$	$\mu\text{A}$
supply current	$I_{CC}$	3.6V	$V_I = V_{CC}$ or GND; $I_O = 0\text{A}$	-	-	40	$\mu\text{A}$
additional supply current	$\Delta I_{CC}$	2.7V to 3.6V	per input pin; $V_I = V_{CC} - 0.6\text{V}$ ; $I_O = 0\text{A}$	-	-	5000	$\mu\text{A}$

### 3.3.3. AC Characteristics 1

( $T_{amb} = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ , voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	V <sub>CC</sub>	Conditions	Min.	Typ. <sup>[1]</sup>	Max.	Unit
CP to Qn propagation delay	$t_{PLH}, t_{PHL}$	1.2V	see Figure 4	-	18	-	ns
		1.65V to 1.95V		2.5	9.7	19.2	ns
		2.3V to 2.7V		1.8	4.9	9.9	ns
		2.7V		1.5	4.5	8.4	ns
		3.0V to 3.6V		1.5	4.1	8.2	ns
$\overline{\text{MR}}$ to Qn propagation delay	$t_{PLH}, t_{PHL}$	1.2V	see Figure 5	-	18	-	ns
		1.65V to 1.95V		2.4	10.2	20.4	ns
		2.3V to 2.7V		1.7	5.2	10.5	ns
		2.7V		1.5	4.7	8.9	ns
		3.0V to 3.6V		1.5	4.3	8.7	ns
clock HIGH or LOW; pulse width	$t_w$	1.65V to 1.95V	see Figure 4	6.0	-	-	ns
		2.3V to 2.7V		5.0	-	-	ns
		2.7V		5.0	1.8	-	ns
		3.0V to 3.6V		4.0	1.2	-	ns
master reset LOW; pulse width	$t_w$	1.65V to 1.95V	see Figure 5	6.0	-	-	ns
		2.3V to 2.7V		5.0	-	-	ns
		2.7V		5.0	1.7	-	ns
		3.0V to 3.6V		4.0	1.2	-	ns
$\overline{\text{MR}}$ to CP; recovery time	$t_{rec}$	1.65V to 1.95V	see Figure 5	2.0	-	-	ns
		2.3V to 2.7V		2.0	-	-	ns
		2.7V		2.0	-1.0	-	ns
		3.0V to 3.6V		2.0	-1.0	-	ns
Dn to CP set-up time	$t_{su}$	1.65V to 1.95V	see Figure 7	5.0	-	-	ns
		2.3V to 2.7V		3.5	-	-	ns
		2.7V		3.0	1.0	-	ns
		3.0V to 3.6V		1.0	0.0	-	ns
Dn to CP hold time	$t_h$	1.65V to 1.95V	see Figure 7	3.0	-	-	ns
		2.3V to 2.7V		2.5	-	-	ns
		2.7V		2.0	-0.2	-	ns
		3.0V to 3.6V		1.0	0.0	-	ns

Note:



[1] Typical values are measured at  $T_{amb}=25^{\circ}C$  and  $V_{CC}=1.2V, 1.8V, 2.5V, 2.7V,$  and  $3.3V$  respectively.

### 3.3.4、AC Characteristics 2

( $T_{amb}=-40^{\circ}C$  to  $+125^{\circ}C$ , voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	V <sub>CC</sub>	Conditions	Min.	Typ.	Max.	Unit
CP to Qn propagation delay	t <sub>PLH</sub> , t <sub>PHL</sub>	1.65V to 1.95V	see Figure 4	2.5	-	22.2	ns
		2.3V to 2.7V		1.8	-	11.4	ns
		2.7V		1.5	-	10.5	ns
		3.0V to 3.6V		1.5	-	10.5	ns
MR to Qn propagation delay		see Figure 5	1.65V to 1.95V	2.4	-	23.5	ns
			2.3V to 2.7V	1.7	-	12.1	ns
			2.7V	1.5	-	11.5	ns
			3.0V to 3.6V	1.5	-	11.0	ns
clock HIGH or LOW; pulse width	t <sub>w</sub>	1.65V to 1.95V	see Figure 4	6.0	-	-	ns
		2.3V to 2.7V		5.0	-	-	ns
		2.7V		5.0	-	-	ns
		3.0V to 3.6V		4.0	-	-	ns
master reset LOW; pulse width		see Figure 5	1.65V to 1.95V	6.0	-	-	ns
			2.3V to 2.7V	5.0	-	-	ns
			2.7V	5.0	-	-	ns
			3.0V to 3.6V	4.0	-	-	ns
MR to CP; recovery time	t <sub>rec</sub>	1.65V to 1.95V	see Figure 5	2.0	-	-	ns
		2.3V to 2.7V		2.0	-	-	ns
		2.7V		2.0	-	-	ns
		3.0V to 3.6V		2.0	-	-	ns
Dn to CP set-up time	t <sub>su</sub>	1.65V to 1.95V	see Figure 6	5.0	-	-	ns
		2.3V to 2.7V		3.5	-	-	ns
		2.7V		3.0	-	-	ns
		3.0V to 3.6V		1.0	-	-	ns
Dn to CP hold time	t <sub>h</sub>	1.65V to 1.95V	see Figure 6	3.0	-	-	ns
		2.3V to 2.7V		2.5	-	-	ns
		2.7V		2.0	-	-	ns
		3.0V to 3.6V		1.0	-	-	ns



## 4、Testing Circuit

### 4.1、AC Testing Circuit




Figure 3. Test circuit for measuring switching times

Definitions for test circuit:

$R_L$  = Load resistance.

$C_L$  = Load capacitance including jig and probe capacitance.

### 4.2、Test Data

Supply voltage	Input		Load		$V_{EXT}$		
	$V_I$	$t_r, t_f$	$C_L$	$R_L$	$t_{PLH}, t_{PHL}$	$t_{PLZ}, t_{PZL}$	$t_{PHZ}, t_{PZH}$
1.2V	$V_{CC}$	$\leq 3.0ns$	30pF	1k $\Omega$	open	$2 \times V_{CC}$	GND
1.65V to 1.95V	$V_{CC}$	$\leq 3.0ns$	30pF	1k $\Omega$	open	$2 \times V_{CC}$	GND
2.3V to 2.7V	$V_{CC}$	$\leq 3.0ns$	30pF	500 $\Omega$	open	$2 \times V_{CC}$	GND
2.7V	2.7V	$\leq 3.0ns$	50pF	500 $\Omega$	open	$2 \times V_{CC}$	GND
3.0V to 3.6V	2.7V	$\leq 3.0ns$	50pF	500 $\Omega$	open	$2 \times V_{CC}$	GND



4.3、AC Testing Waveforms




Figure 4. Input (Dn) to output (Qn) propagation delays




Figure 5. Clock (CP) to output (Qn) propagation delays, the clock pulse width, and the maximum frequency




Figure 6. Data set-up and hold times for the data input (Dn)




## 4.4. Measurement Points

Supply voltage	Input	Output		
		$V_M$	$V_X$	$V_Y$
$V_{CC}$	$V_M$	$V_M$	$V_X$	$V_Y$
1.2V	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL}+0.15V$	$V_{OH}-0.15V$
1.65V to 1.95V	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL}+0.15V$	$V_{OH}-0.15V$
2.3V to 2.7V	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL}+0.15V$	$V_{OH}-0.15V$
2.7V	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL}+0.3V$	$V_{OH}-0.3V$
3.0V to 3.6V	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL}+0.3V$	$V_{OH}-0.3V$



## 5、Package Information




### 5.1、SOP20



Symbol	Dimensions (mm)	
	Min.	Max.
A	2.47	2.65
A1	0.05	0.30
A2	2.20	2.44
b	0.35	0.50
c	0.15	0.30
D	12.54	12.94
E	10.00	10.60
E1	7.30	7.70
e	1.27	
L	0.40	1.05
L1	1.30	1.50
$\theta$	0°	8°




## 5.2、TSSOP20



Symbol	Dimensions (mm)	
	Min.	Max.
A	-	1.20
A1	0.05	0.15
A2	0.80	1.05
b	0.19	0.30
c	0.09	0.20
D	6.40	6.60
E1	4.30	4.50
E	6.20	6.60
e	0.65	
L	0.45	0.75
L1	1.00	
$\theta$	0°	8°



## 5.3、DHVQFN20



Symbol	Dimensions (mm)	
	Min.	Max.
A	0.80	1.00
A1	0.00	0.05
A2	0.60	0.70
A3	0.20	
D	4.40	4.60
E	2.40	2.60
e	0.50	
b	0.18	0.30
L	0.30	0.50
D1	2.70	3.15
E1	0.70	1.15



## 6、 Statements And Notes

### 6.1、 The name and content of Hazardous substances or Elements in the product

Part name	Hazardous substances or Elements									
	Lead and lead compounds	Mercury and mercury compounds	Cadmium and cadmium compounds	Hexavalent chromium compounds	Polybrominated biphenyls	Polybrominated biphenyl ethers	Dibutyl phthalate	Butylbenzyl phthalate	Di-2-ethylhexyl phthalate	Diisobutyl phthalate
Lead frame	○	○	○	○	○	○	○	○	○	○
Plastic resin	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
The lead	○	○	○	○	○	○	○	○	○	○
Plastic sheet installed	○	○	○	○	○	○	○	○	○	○
explanation	○: Indicates that the content of hazardous substances or elements in the detection limit of the following the SJ/T11363-2006 standard. ×: Indicates that the content of hazardous substances or elements exceeding the SJ/T11363-2006 Standard limit requirements.									

### 6.2、 Notes

We recommend you to read this chapter carefully before using this product.

The information in this chapter is provided for reference only and i-Core disclaims any express or implied warranties, including but not limited to applicability, special application or non-infringement of third party rights.

This product is not suitable for critical equipment such as life-saving, life-sustaining or safety equipment. It is also not suitable for applications that may result in personal injury, death, or serious property or environmental damage due to product malfunction or failure. I-Core will not be liable for any damages incurred by the customers at their own risk for such applications.

The customer is responsible for conducting all necessary tests i-Core's application to avoid failure in the application or the application of the customer's third party users. I-Core does not accept any liability.

The Company reserves the right to change or improve the information published in this chapter at any time. The information in this chapter are subject to change without notice. We recommend the customer to consult our sales staff before purchasing.

Please obtain related materials form i-Core's regular channels and we are not responsible for its content if it is provided by sources other than our company.

In case of any conflict between the Chinese and English version, the version is subject to the Chinese one.